



Ultracoat Sport Color

**One-component
water-based coloured
acrylic paint for marking
out playing areas on
wooden sports surfaces**



WHERE TO USE

Ultracoat Sport Color is a one-component, water-based, coloured acrylic paint used in combination with **Ultracoat HT Sport** for marking out playing areas on wooden sports surfaces.

Ultracoat Sport Color is used to mark out the lines inside courts and pitches and to paint the side-lines and playing zones of courts and pitches. **Ultracoat Sport Color** has excellent covering, adhesion and levelling properties and does not need to be sanded before applying the next coat. **Ultracoat Sport Color** is available in 8 different colours: black, white, dark blue, light blue, orange, yellow, red and green.

RECOMMENDATIONS

- Never use **Ultracoat Sport Color** as final treatment on wooden floors. **Ultracoat Sport Color** may be diluted with up to 10% of water. Some types of rubber-based adhesive tape used for marking out courts and pitches contain plasticizers that could damage the coat of paint. It is recommended to use tape with low adhesion properties removing the tape as soon as possible, and in all cases before the paint is completely dry.
- Use, store and transport **Ultracoat Sport Color** at a temperature of +10°C to +25°C.
- Do not use on external surfaces.
- Use only clean containers and tools.
- Use in combination with **Ultracoat Premium Base** and **Ultracoat HT Sport**.
- Completely remove all traces of previous treatments in order to obtain an even finish.

- Protect treated surfaces from direct sunlight and draughts for the first 3 hours after application.
- Leftovers of the product must not be put back into its container. Partially-used containers must not be stored for long periods.

APPLICATION PROCEDURE

Open the container by removing the cover and lever-lock band and mix the product thoroughly.

Put the cover and lever-lock band back on the drum, open the red cap and insert the filter.

Before painting the lines or zones, treat the surface with products from the **Ultracoat** range (follow the instructions contained in the **Ultracoat HT Sport** Technical Data Sheet).

It is recommended to use suitable adhesive tape to mark out the side-lines and playing zones of the court or pitch. Make sure it is firmly attached to the surface so that the paint is left with a neat edge. We advise against using "marine tape".

Use a roller to apply **Ultracoat Sport Color** after applying a coat of **Ultracoat Premium Base** and a coat of **Ultracoat HT Sport** (refer to the relative Technical Data Sheets).

Apply a coat of **Ultracoat Sport Color** after sanding the surface with sandpaper or a 220 grade grid, using **Ultracoat Roller Sport Finish**.

Paint the entire surface with 1 or 2 coats of **Ultracoat Sport Color** depending on how deep is the coverage of the colour you require. Wait around 1-2 hours between each coat; no sanding is required. If a third coat is required, it is recommended to lightly sand the surface beforehand with **Ultracoat Pad Special Stripper**.

Ultracoat Sport Color



Remove the protective cap and mix the product accurately



Remove the red cap, pull out the expansion bellow and insert the filter



When the colour is almost dry remove the protective demarcation band

TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Consistency:	liquid
Colour:	various colours
Density:	1.05/1.1 depending on the colour
Cps viscosity:	600-1000 depending on the colour
Sanding:	after 2 hours
Maximum permitted dilution ratio (Dir. 2004/42/CEE):	10% with clean water

It is recommended to schedule the work in order to prevent waiting more than 24 hours between each coat of **Ultracoat Sport Color**.

2 hours and no more than 24 hours after applying the last coat of Ultracoat Sport Color, apply the final coat of Ultracoat HT Sport, without sanding.

Cleaning

Tools and residues of **Ultracoat Sport Color** may be cleaned with water while the product is still wet. Once hardened, the product may only be removed mechanically.

CONSUMPTION

80-100 ml/m² per coat.

PACKAGING

5 kg tub.

STORAGE

12 months in its original, sealed packaging in a dry place.

SAFETY INSTRUCTIONS FOR PREPARATION AND APPLICATION

Ultracoat Sport Color is not considered hazardous according to current norms and guidelines regarding the classification of mixtures. It is recommended to use protective gloves and goggles and to take the usual precautions for handling chemicals. If the product is applied in closed areas make sure they are well ventilated. For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.

All relevant references for the product are available upon request and from www.mapei.com



BUILDING THE FUTURE