PRODUCT-DETAILS

XT2S 160 Ekip LS/I In=10A 4p F F

XT2S 160 Ekip LS/I In=10A 4p F F



Información General

Extended Product Type	XT2S 160 Ekip LS/I In=10A 4p F F
Product ID	1SDA067833R1
EAN	8015644017293
Catalog Description	XT2S 160 Ekip LS/I In=10A 4p F F
Long Description	C.BREAKER TMAX XT2S 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-LS/I R 10 A

Clasificación

EAN	8015644017293
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensiones

Product Net Width	120 mm
Product Net Height	130 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	1.5 kg

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	130 mm
Package Level 1 Height	208 mm
Package Level 1 Depth / Length	145 mm
Package Level 1 Gross Weight	1.6 kg
Package Level 1 EAN	8015644017293

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Información Adicional

Circuit Breaker Type to be Associated	Power Distribution
Current Type	AC
Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	Nr. Operations 240 cycles per hour Nr. Operations 25000 cycle
Number of Poles	4
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	10 A
Rated Frequency (f)	50 / 60 Hz
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA
Rated Uninterrupted Current (I_u)	160 A
Release	Ekip LS/I
Release Type	EL
Short-Circuit	S

Performance Level	
Standards	IEC
Sub-type	XT2
Terminal Connection Type	Fixed Circuit-Breakers
Version	F

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	1SDC210100D0205 1SDC210099D0205
Declaration of Conformity - CE	9AKK106713A5901
Environmental Information	1SDL000190R0001
GL Certificate	1SDL000163R0093
Instructions and Manuals	1SDH000721R0001
LR Certificate	1SDL000163R0100

Clasificaciones

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax XT



