PRODUCT-DETAILS

XT2V 160 BREAKING PART 3p F F

XT2V 160 BREAKING PART 3p F F



Información General

Extended Product Type	XT2V 160 BREAKING PART 3p F F
Product ID	1SDA068167R1
EAN	8015644696153
Catalog Description	XT2V 160 BREAKING PART 3p F F
Long Description	BREAKING PART TMAX XT2V 160 FIXED THREE-POLE WITH FRONT TERMINALS

Clasificación

EAN	8015644696153
Minimum Order Quantity	1 piece
Customs Tariff Number	85362090

Dimensiones

Product Net Width	90 mm
Product Net Height	130 mm
Product Net Depth / Length	82.5 mm
Product Net Weight	0.82 kg

Información de Embalaje

Package Level 1 Units	1 piece

Package Level 1 Width	150 mm
Package Level 1 Height	215 mm
Package Level 1 Depth / Length	135 mm
Package Level 1 Gross Weight	0.92 kg
Package Level 1 EAN	8015644696153

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Información Adicional

Electrical Durability	120 cycles per hour 8000 cycle
Mechanical Durability	Nr. Operations 240 cycles per hour Nr. Operations 25000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CBBU
Rated Frequency (f)	50 / 60 Hz
Rated Voltage (U_r)	690 V
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC 500 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 200 kA (230 V AC) 200 kA (240 V AC) 200 kA (380 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 70 kA (525 V AC) 50 kA (690 V AC) 15 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 3 Poles in Series 100 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 200 kA (230 V AC) 200 kA (240 V AC) 200 kA (380 V AC) 150 kA (415 V AC) 150 kA (440 V AC) 150 kA (500 V AC) 70 kA (525 V AC) 50 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 100 kA (500 V DC) 3 Poles in Series 100 kA
Rated Uninterrupted Current (I_u)	160 A
Short-Circuit Performance Level	V
Standards	IEC
Sub-type	XT2
Terminal Connection	Fixed Circuit-Breakers

Type	
Version	F

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	1SDC210100D0205 1SDC210099D0205
Declaration of Conformity - CE	9AKK106713A5901
Environmental Information	1SDL000190R0001
GL Certificate	1SDL000163R0093
Instructions and Manuals	1SDH000721R0001
LR Certificate	1SDL000163R0100

Clasificaciones

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
UNSPSC	39120000
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax XT



