PRODUCT-DETAILS

# XT5H 400 Ekip Dip LS/I In=400 4p F F

## XT5H 400 Ekip Dip LS/I In=400 4p F F



### Información General

| | |
|---|---|
| Extended Product Type | XT5H 400 Ekip Dip LS/I In=400 4p F F |
| Product ID | 1SDA100528R1 |
| EAN | 8056221006040 |
| Catalog Description | XT5H 400 Ekip Dip LS/I In=400 4p F F |
| Long Description | C.BREAKER TMAX XT5H 400 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP DIP LS/I R 400 |

### Clasificación

| | |
|---|---|
| EAN | 8056221006040 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362090 |

### Dimensiones

| | |
|---|---|
| Product Net Width | 186 mm |
| Product Net Height | 205 mm |
| Product Net Depth / Length | 103.5 mm |
| Product Net Weight | 6.4 kg |

### Información de Embalaje

| | |
|---|---|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 250 mm |
| Package Level 1 Height | 245 mm |
| Package Level 1 Depth / Length | 285 mm |
| Package Level 1 Gross Weight | 6.888 kg |
| Package Level 1 EAN | 8056221006040 |

## Ambiente

| | |
|---|---|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Información Adicional

| | |
|---|---|
| Circuit Breaker Type to be Associated | Power Distribution |
| Current Type | AC |
| Electrical Durability | 120 cycles per hour<br>7000 cycle |
| Mechanical Durability | 240 cycles per hour<br>20000 cycle |
| Number of Poles | 4 |
| Order Multiple | 1 piece |
| Power Loss | 19 W |
| Product Main Type | SACE Tmax XT |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | CB |
| Rated Current ($I_n$) | 400 A |
| Rated Impulse Withstand Voltage ($U_{imp}$) | 8 kV |
| Rated Insulation Voltage ($U_i$) | 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 50 kA<br>(690 V AC) 40 kA |
| Rated Short-time Withstand Current ($I_{cw}$) | 6 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 50 kA<br>(690 V AC) 40 kA |
| Rated Uninterrupted Current ($I_u$) | 400 A |
| Release | Ekip Dip LS/I |
| Release Type | EL |
| Short-Circuit Performance Level | H |

| | |
|---|---|
| Standards | IEC 60947 |
| Sub-type | XT5 |
| Terminal Connection Type | Fixed Circuit-Breakers |
| Version | F |

## Certificados y Declaraciones (Número de Documento)

| | |
|---|---|
| Data Sheet, Technical Information | 1SDC210100D0205<br>1SDC210099D0205 |
| Declaration of Conformity - CE | 9AKK107680A2824 |
| Instructions and Manuals | 1SDH002011A1001 |

## Clasificaciones

| | |
|---|---|
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

## Categorias

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax XT



