
PRODUCT-DETAILS

XT5N 400 BREAKING PART 4p F F

XT5N 400 BREAKING PART 4p F F



Información General

Extended Product Type	XT5N 400 BREAKING PART 4p F F
Product ID	1SDA100552R1
EAN	8056221006286
Catalog Description	XT5N 400 BREAKING PART 4p F F
Long Description	BREAKING PART TMAX XT5N 400 FIXED FOUR-POLE WITH FRONT TERMINALS

Clasificación

EAN	8056221006286
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensiones

Product Net Width	186 mm
Product Net Height	205 mm
Product Net Depth / Length	103.5 mm
Product Net Weight	4.55 kg

Información de Embalaje

Package Level 1 Units	1 piece

Package Level 1 Width	248 mm
Package Level 1 Height	240 mm
Package Level 1 Depth / Length	285 mm
Package Level 1 Gross Weight	4.5 kg
Package Level 1 EAN	8056221006286

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Información Adicional

Electrical Durability	120 cycles per hour 7000 cycle
Mechanical Durability	240 cycles per hour 20000 cycle
Number of Poles	4
Order Multiple	1 piece
Product Main Type	SACE Tmax XT
Product Name	Moulded Case Circuit Breaker
Product Type	CBBU
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC 750 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 25 kA (500 V DC) 2 Poles in Series 25 kA
Rated Short-time Withstand Current (I_{cw})	6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 70 kA (230 V AC) 70 kA (240 V AC) 70 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (500 V AC) 25 kA (525 V AC) 25 kA (690 V AC) 20 kA (250 V DC) 2 Poles in Series 25 kA (500 V DC) 2 Poles in Series 25 kA
Rated Uninterrupted Current (I_u)	400 A
Short-Circuit Performance Level	N
Standards	IEC 60947
Sub-type	XT5
Terminal Connection Type	Fixed Circuit-Breakers
Version	F

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	1SDC210100D0205 1SDC210099D0205
Declaration of Conformity - CE	9AKK107680A2824
Instructions and Manuals	1SDH002011A1001

Clasificaciones

ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax XT

