
PRODUCT-DETAILS

DS804P-C125/0.3A

DS804P-C125/0.3A Residual Current Circuit Breaker with Overcurrent Protection



Información General

Tipo de producto extendido	DS804P-C125/0.3A
Código de producto	2CCG001319R0001
EAN	7612271517885
Descripción corta	DS804P-C125/0.3A Residual Current Circuit Breaker with Overcurrent Protection
Descripción larga	The DS800 series residual circuit breaker with overcurrent protection (RCBO) is available as 2P, 3P and 4P device. It is for protection of end user against overload and short-circuit currents. The DS800 range offers several types of protection. Type A (pulse current sensitive residucal current protection device), type AC (alternating current sensitive residucal current protection devcie), type AS (pulse current sensitive residual current protection device - selective) and tpye A-AP-R (pulse current sensitive residual current protection devcie - short-time delay).

Technical

Normas	IEC 60947-2
Característica de tropiezo	C
Tensión nominal de operación	230 / 415 V AC
Corriente nominal (I_n)	125 A

© 2024 ABB. All rights reserved.

Corriente nominal de funcionamiento (I_e)	125 A
Corriente residual nominal	300 mA
Capacidad nominal de corte en cortocircuito (I_{cu})	50 kA
Capacidad de rotura máxima	50 kA
Capacidad nominal de corte en cortocircuito en servicio (I_{cs})	40 kA
Frecuencia nominal (f)	50 … 60 Hz
Pérdida de potencia	55.1 W
Número de postes protegidos	4
Número de polos	4
Número de interruptores de fuga a tierra (ELCB)	1
Características de funcionamiento	Instantaneous
Tipo de desbloqueo	C
Accesorios disponibles	Yes

Material Compliance

Información sobre RoHS	2CCC413008D0206
Estado de RoHS	Following EU Directive 2002/95/EC August 18, 2005 and amendment
Fecha de RoHS	20170426
Declaración REACH	9AKK108468A1490
Plantilla de notificación de minerales de conflicto (CMRT)	9AKK108468A3363

Technical UL/CSA

Capacidad de corriente de cortocircuito (SCCR)	300 mA

Dimensiones

Ancho del product	227.5 mm
Alto del producto	108.2 mm
Largo del product	82.3 mm
Peso del product	1757 g

Clasificación

Embalaje Nivel 1 Unidades	box 1 piece

© 2024 ABB. All rights reserved.

Embalaje Nivel 1 Peso	1757 g

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	9AKK108468A1488
Declaración de conformidad - UKCA	9AKK108468A1489

Installation

Instrucciones y manuales	9AKK108467A9515

Descargas Populares

Ficha técnica, información técnica	9AKK107991A8329

Clasificaciones

ETIM 8	EC002281 - Distributor assembly with combination RCCB/MCB
ETIM 9	EC002281 - Distributor assembly with combination RCCB/MCB
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020

Categorias

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Interruptores diferenciales → Interruptores diferenciales combinados

© 2024 ABB. All rights reserved.





© 2024 ABB. All rights reserved.