PRODUCT-DETAILS

S802C-B40

Int.aut. S802C-B40 2p 40A B 25kA



Información General

Extended Product Type	S802C-B40
Product ID	2CCS882001R0405
EAN	7612271213053
Catalog Description	Int.aut. S802C-B40 2p 40A B 25kA
Long Description	The S802C-B40 is a 2-pole High Performance Circuit breaker with B-characteristic, with cage terminal and a rated current of 40 A. It is a current limiting device with a maximum breaking capacity of 25kA at 240/415V. It can be used for voltages up to 254/440V and in DC as well. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S802C-B40 complies with IEC/EN 60898-1 and IEC/EN 60947-2 and allows the use for residential, commercial and industrial applications. It has numerous of approvals, therefore it can be used worldwide. The extensive range of accessory makes the use of S802C-B40 more comfortable. Due to the fast arc extinction of S802C-B40 your application will be secured.

Technical

Standards	IEC/EN 60947-2 IEC/EN 60898-1 UL 1077
Number of Poles	2
Number of Protected Poles	2
Tripping Characteristic	B
Rated Current (I_n)	40 A
Rated Operational Voltage	254/440 V AC 250 V DC

Power Loss	7.4 W at Rated Operating Conditions per Pole 3.7 W
Rated Insulation Voltage (U_i)	500 V AC
Operational Voltage	Maximum 230/400 V AC Minimum 12 V AC
Rated Frequency (f)	50...60 Hz
Rated Short-Circuit Capacity (I_{cn})	(400 V) 15 kA (230 V) 15 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 / 415 V AC) 25 kA (254 / 440 V AC) 15 kA (250 V DC) 10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 / 415 V AC) 18 kA (254 / 440 V AC) 10 kA (125 V DC) 10 kA
Energy Limiting Class	3
Overvoltage Category	IV
Pollution Degree	3
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Housing Material	Insulation group I, RAL 7035
Actuator Marking	I / O
Contact Position Indication	ON / OFF / TRIP
Degree of Protection	IP20
Remarks	Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captive screw
Electrical Endurance	6000 cycle
	4000 cycle
Terminal Type	Screw Terminals
Connecting Capacity	Rigid 0 ... 50 mm² Flexible 0 ... 70 mm²
Tightening Torque	3.5 N·m 31 in·lb
Recommended Screw Driver	Pozidriv 2
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	Any
Built-In Depth (t_2)	82.5 mm

Ambiente

Ambient Air Temperature	Funcionamiento -25...60 °C
Reference Ambient Air Temperature	acc. to IEC60947-2 30 °C acc. to EN60898-1 30 °C
Resistance to Shock acc. to IEC 60068-2-27	5 g 30 ms
Resistance to Vibrations acc. to IEC 60068-2-6	2 - 13.2 Hz / 1mm 13.2 - 100Hz / 0.7g with load 100% x Ie
Environmental Conditions	Damp Heat Cyclic acc. to IEC 60068-2-30 12+12 cycle Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96% Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100% Dry Heat Test B acc. to IEC 60068-2-2 16 hour @ 55 °C Dry Heat Test B acc. to IEC 60068-2-2 2 hour @ 70 °C
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Interrupting Rating acc.	(480Y / 277 V AC) 10 kA

to UL1077	(250 V DC) 10 kA

Dimensiones

Product Net Width	54 mm
Product Net Depth / Length	82.5 mm
Product Net Height	95 mm
Product Net Weight	490 g

Información de Embalaje

Package Level 1 Units	box 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	60 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	510 g
Package Level 1 EAN	7612271213053

Clasificación

Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CCC413016D0601
Environmental Information	2CCY413207D0203
Instructions and Manuals	2CCC413016M0008
RoHS Information	2CCC413016D0601 9AKK107680A3903

Descargas Populares

Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413016M0008
Dimension Diagram	2CCC413003C0201

Clasificaciones

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)

Categorias

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Interruptores automáticos alto rendimiento HPCBs

