

PRODUCT-DETAILS

A42 552-120

Active Energy Class $\pm 0,5\%$ (or C for MID meters). Reactive Energy Class $\pm 2\%$;



Información General

Extended Product Type	A42 552-120
Product ID	2CMA170518R1000
ABB Type Designation	A42 552-120
EAN	7392696705189
Catalog Description	Active Energy Class $\pm 0,5\%$ (or C for MID meters). Reactive Energy Class $\pm 2\%$;

Long Description	<p>Advanced DIN-rail meter with a large and easy to read back lighted pixel-oriented display. The meter is intended for use in the industry, commercial buildings etc. The meter can be used in 3 or 4 wire systems with a wide voltage range. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase transformer connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Internal clock for tariff shift, Min and maximum demand, previous values and event log with timestamps. 8 channel load profile Four programmable inputs or outputs. Up to the 16th harmonics for pulses or alarm etc. RS-485 communication over Modbus RTU or EQ Bus. Accuracy class 0,5 (or C for MID meters). The meters is IEC approved + MID approved and verified. Version for use in 690 V application.</p>
------------------	--

Clasificación

E-Number (Sweden)	0980698
EAN	7392696705189
Minimum Order Quantity	1 piece
Customs Tariff Number	90283011

Dimensiones

Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.207 kg

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	68 mm
Package Level 1 Depth / Length	94 mm
Package Level 1 Gross Weight	0.279 kg
Package Level 1 EAN	7392696705189

Ambiente

Ambient Air Temperature	Funcionamiento -40 ... +70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Información Adicional

Accuracy	Active Energy Class $\pm 0,5\%$ (or C for MID meters). Reactive Energy Class $\pm 2\%$.
Communication Interface	RS-485
Communication	MODBUS RTU
Connecting Capacity Main Circuit	0.5 ... 10 mm ²
Current Rating	6 A
Degree of Protection	IP20
Enclosure Material	Plastic
Frequency (f)	50 ... 60 Hz
Function	Electricity meter
Meter Type	Transformer connected
Mounting Type	DIN rail
Number of Phases	1
	0.801 W
Product Main Type	A42
Product Name	Contador de energía
Rated Current (I_n)	6 A
Rated Voltage (U_r)	(Un) N-L 57.7 ... 288 V
RoHS Date	2011-44
Standards	IEC 62053-23
Sub-Function	Platinum

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	2CMC484002M0201
Declaration of Conformity - CE	2CMC484002D0001
Environmental Information	2CMC484005D0001
Instructions and Manuals	2CMC484010M4901
RoHS Information	2CMC484006

Clasificaciones

ETIM 4	EC001506 - Electronic kilowatt-hour meter
ETIM 5	EC001506 - Kilowatt-hour meter
ETIM 6	EC001506 - Kilowatt-hour meter
ETIM 7	EC001506 - Kilowatt-hour meter
Object Classification Code	P
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorías

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Contadores eléctricos para perfil DIN → Contadores eléctricos

