PRODUCT-DETAILS

# UK612N2

# UK612N2 con. unit fl 12M IP30 w. door



## Información General

| | |
|---|---|
| Extended Product Type | UK612N2 |
| Product ID | 2CPX031369R9999 |
| EAN | 4011617313694 |
| Catalog Description | UK612N2 con. unit fl 12M IP30 w. door |
| Long Description | Consumer unit, series UK600, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, powder-coated, in RAL 9016, enclosure out of thermoplast, with trim frame and metal door, door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 372 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 372 x 384 x 9, 1-rows, Space units 12, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE Quick-terminal, cable fastening rail integrated, assembled with device carrier, device support removable |

## Clasificación

| | |
|---|---|
| E-Number (Sweden) | 2201236 |
| EAN | 4011617313694 |
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85381000 |

## Dimensiones

| | |
|---|---|
| Product Net Width | 384 mm |
| Product Net Height | 372 mm |
| Product Net Depth / Length | 97 mm |
| Product Net Weight | 2.495 kg |

## Información de Embalaje

| | |
|---|---|
| Package Level 1 Units | pack 1 piece |
| Package Level 1 Width | 390.000 mm |
| Package Level 1 Height | 380.000 mm |
| Package Level 1 Depth / Length | 115.000 mm |
| Package Level 1 Gross Weight | 2.595 kg |
| Package Level 1 EAN | 4011617313694 |
| Package Level 2 Units | pallet (lift) 90 piece |
| Package Level 2 Width | 800.000 mm |
| Package Level 2 Height | 1820.000 mm |
| Package Level 2 Depth / Length | 1200.000 mm |
| Package Level 2 Gross Weight | 244.55 kg |

## Información Adicional

| | |
|---|---|
| Color | White |
| Configuration Type | assembled with device carrier |
| Cover Plate Type | Door |
| Degree of Protection | IP30 |
| DIN Place Units | 12 |
| Enclosure Type | Consumer unit |
| Housing Material | Plastic |
| Interior Depth | 75 mm |
| Mounting Type | Flush-mounted |
| Niche Depth | 95 mm |
| Niche Height | 355 mm |
| Niche Width | 367 mm |
| Number of Rows | 1 |
| Power Loss | Δt = 30K 31 W |
| Product Main Type | UK |
| Product Name | UK612N2 con. unit fl 12M IP30 w. door |
| Protection Class | Isolated |
| Rated Operational Voltage | Maximum 400 V |
| Terminal Type | Quick-Terminal |

## Certificados y Declaraciones (Número de Documento)

| | |
|---|---|
| Data Sheet, Technical Information | 2CPC000001C0101<br>2CPC000002C0101<br>2CPC000031C0101<br>2CPC000187C0101<br>2CPC000188C0101 |
| Declaration of Conformity - CE | No declaration needed |
| Instructions and Manuals | 2CPC129380M5601 |

## Clasificaciones

| | |
|---|---|
| ETIM 5 | EC000214 - Small distribution board |
| ETIM 6 | EC000214 - Small distribution board |
| ETIM 7 | EC000214 - Small distribution board |
| Object Classification Code | U |
| WEEE Category | 4. Large Equipment (Any External Dimension More Than 50 cm) |

## Categorias

Productos y sistemas de baja tensión → Envolventes y sistemas de cableado → Cajas de distribución → Cajas de distribución de empotrar

