PRODUCT-DETAILS

UK636NB

UK636NB con. unit fl 36M IP30 base



Información General

Extended Product Type	UK636NB
Product ID	2CPX031376R9999
EAN	4011617313762
Catalog Description	UK636NB con. unit fl 36M IP30 base
Long Description	Consumer unit, series UK600, for the internal use, without closed cover without door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, IK code 07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, in RAL 9016, enclosure out of thermoplast, without cover and without door, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 597 x 362 x 97, 3-rows, Space units 36, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE Quick-terminal, cable fastening rail integrated, assembled with device carrier, device support removable

Clasificación

E-Number (Sweden)	2201241
EAN	4011617313762
Minimum Order Quantity	1 piece
Customs Tariff Number	85371098

Dimensiones

Product Net Width	362 mm
Product Net Height	597 mm
Product Net Depth / Length	97 mm
Product Net Weight	2.615 kg

Información de Embalaje

Package Level 1 Units	pack 1 piece
Package Level 1 Width	390.000 mm
Package Level 1 Height	630.000 mm
Package Level 1 Depth / Length	115.000 mm
Package Level 1 Gross Weight	2.72 kg
Package Level 1 EAN	4011617313762
Package Level 2 Units	pallet (lift) 45 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1820.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	137.675 kg

Información Adicional

Color	White
Configuration Type	assembled with device carrier
Cover Plate Type	optional
Degree of Protection	IP30
DIN Place Units	36
Enclosure Type	Consumer unit
Housing Material	Plastic
Interior Depth	75 mm
Mounting Type	Flush-mounted
Niche Depth	95 mm
Niche Height	605 mm
Niche Width	367 mm
Number of Rows	3
Power Loss	Δt = 30K 54 W
Product Main Type	UK
Product Name	UK636NB con. unit fl 36M IP30 base
Protection Class	Isolated
Rated Operational Voltage	Maximum 400 V
Terminal Type	Quick-Terminal

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101 2CPC000031C0101 2CPC000187C0101 2CPC000188C0101
Declaration of Conformity - CE	No declaration needed
Instructions and Manuals	2CPC129380M5601

Clasificaciones

ETIM 5	EC000214 - Small distribution board
ETIM 6	EC000214 - Small distribution board
ETIM 7	EC000214 - Small distribution board
Object Classification Code	U
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Envolventes y sistemas de cableado → Cajas de distribución → Cajas de distribución de empotrar

