PRODUCT-DETAILS

# F204 B-125/0.03-L

## Int.dif.F204B-125/0,03 4p 125A B 30mA



### Información General

| | |
|---|---|
| Extended Product Type | F204 B-125/0.03-L |
| Product ID | 2CSF204523R1950 |
| EAN | 8012542988700 |
| Catalog Description | Int.dif.F204B-125/0,03 4p 125A B 30mA |
| Long Description | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. This product is particularly suitable for the protection against smooth d.c. earth fault currents. This product is suitable for installations where neutral on the left is . |

### Technical

| | |
|---|---|
| Standards | IEC/EN 61008 |
| Operating Characteristic | Instantaneous |
| Type of Residual Current | B type |
| Rated Residual Current | 30 mA |
| Rated Current ($I_n$) | 125 A |
| Number of Poles | 4 |
| Position of Neutral Terminals | Left |
| Power Loss | at Rated Operating Conditions per Pole 7.5 W |
| Rated Voltage ($U_r$) | 400 V |
| Rated Frequency (f) | 50...60 Hz |

## Ambiente

| | |
|---|---|
| Ambient Air Temperature | Funcionamiento -25...40 °C |
| RoHS Status | Following EU Directive 2011/65/EU |

## Technical UL/CSA

| | |
|---|---|
| Short-Circuit Current Rating (SCCR) | 0.03 mA |

## Dimensiones

| | |
|---|---|
| Product Net Width | 0.072 m |
| Product Net Height | 0.085 m |
| Product Net Depth / Length | 0.069 m |
| Product Net Weight | 0.500 kg |

## Información de Embalaje

| | |
|---|---|
| Package Level 1 Units | 1 piece |
| Package Level 1 Width | 0.073 m |
| Package Level 1 Height | 0.078 m |
| Package Level 1 Depth / Length | 0.09 m |
| Package Level 1 Gross Weight | 0.525 kg |
| Package Level 1 EAN | 8012542988717 |

## Clasificación

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363030 |
| E-Number (Sweden) | 2160009 |

## Certificados y Declaraciones (Número de Documento)

| | |
|---|---|
| Declaration of Conformity - CE | 9AKK106713A5602 |
| Environmental Information | Refer to RoHS |
| Instructions and Manuals | Manual sheet inside the box |
| RoHS Information | 2CSC423001K2702 |

## Descargas Populares

| | |
|---|---|
| Data Sheet, Technical Information | 9AKK107046A0424 |
| Instructions and Manuals | Manual sheet inside the box |

## Clasificaciones

| | |
|---|---|
| Object Classification | Q |

| Code | |
|---|---|
| ETIM 4 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 5 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 6 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 7 | EC000003 - Residual current circuit breaker (RCCB) |

## Categorias

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Interruptores diferenciales → Interruptores diferenciales

