PRODUCT-DETAILS

# DS201 C10 APR30

# I.com.DS200 1p+N C 10A A APR 10kA 30mA




## Información General

| | |
|---|---|
| Extended Product Type | DS201 C10 APR30 |
| Product ID | 2CSR255480R1104 |
| EAN | 8012542399612 |
| Catalog Description | I.com.DS200 1p+N C 10A A APR 10kA 30mA |
| Long Description | The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA). The APR type provides an optimal trade-off between safety and continuity of service, thanks to the resistance to unwanted trippings, offering good protection and isolation of resistive and inductive loads. |

## Technical

| | |
|---|---|
| Standards | IEC/EN 61009-1, IEC/EN 61009-2-1 |
| Type of Residual Current | A type |
| Number of Poles | 2 |
| Number of Protected Poles | 1 |
| Rated Current ($I_n$) | 10 A |
| Rated Current Sensitivity | 0.03 A |
| Rated Voltage ($U_r$) | 230 V |

| | |
|---|---|
| Rated Insulation Voltage ($U_i$) | 500 V |
| Overvoltage Category | III |
| Pollution Degree | 2 |
| Test Voltage (Ut) | 170 … 264 V |
| Rated Frequency (f) | 50 … 60 Hz |
| Rated Short-Circuit Capacity ($I_{cn}$) | 6 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ($I_{cu}$) | 10 kA |
| Rated Service Short-Circuit Breaking Capacity ($I_{cs}$) | 7.5 kA |
| Rated Residual Breaking Capacity (IΔm) | EN 61009-1 6000 A<br>IEC 61009-1 6000 A |
| Primary Rated Impulse Withstand Voltage | 4 kV |
| Dielectric Test Voltage | 2.5 kV |
| Tripping Characteristic | C |
| Energy Limiting Class | 3 |
| Surge Immunity acc. to IEC 61000-4-5 | 3000 A |
| Housing Type | Insulation group I - II, RAL 7035 |
| Actuator Type | Toggle - Insulation group II, Black RAL 9005, sealable in ON-OFF positions |
| Contact Position Indication | Red ON / Green OFF |
| Fault Indication | Blue flag on toggle |
| Electrical Endurance | 10000 cycle |
| | 20000 cycle |
| Degree of Protection | Terminals IP20<br>Housing IP40 |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g / 2 shocks / 13 ms |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 0.1 mm or 1 g - 20 cycles at 5…150…5 Hz |
| Environmental Conditions | 28 cycles<br>with 55 °C / 90-96 %<br>and 25 °C / 95-100 % |
| Reference Ambient Air Temperature | 30 °C |
| Terminal Type | Screw Terminals |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Cable Size | 25 mm² |
| Connecting Capacity | Busbar 10/10 mm²<br>Stranded 0.75 … 25 mm²<br>Flexible with Ferrule 0.75 … 16 mm²<br>Flexible 0.75 … 16 mm² |
| Tightening Torque | 2.8 N·m |
| Wire Stripping Length | 12 mm |
| Mounting Type | on DIN rail EN 60715 (35mm) by means of mounting clip |
| Mounting Position | Any |
| Power Supply Connection | Arbitrary |

| | |
|---|---|
| Position of Neutral Terminals | Right |
| Power Loss | 1.8 W |
| Number of Modular Spacings per DIN Rail | 2 |
| Accessory Type | Auxiliary contact<br>Signal contact / auxiliary contact<br>Shunt trip<br>Auxiliary contact for bottom fitting<br>Undervoltage release<br>Overvoltage release<br>Motor operating device |

## Ambiente

| | |
|---|---|
| Ambient Air Temperature | Funcionamiento -25...55 °C |

## Technical UL/CSA

| | |
|---|---|
| Short-Circuit Current Rating (SCCR) | 0.03 A |

## Dimensiones

| | |
|---|---|
| Product Net Width | 0.035 m |
| Product Net Height | 0.085 m |
| Product Net Depth / Length | 0.069 m |
| Product Net Weight | 0.200 kg |

## Información de Embalaje

| | |
|---|---|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 40 mm |
| Package Level 1 Height | 106 mm |
| Package Level 1 Depth / Length | 80 mm |
| Package Level 1 Gross Weight | 225 g |
| Package Level 1 EAN | 8012542399612 |
| Package Level 2 Units | 5 piece |
| Package Level 2 Width | 200 mm |
| Package Level 2 Height | 106 mm |
| Package Level 2 Depth / Length | 80 mm |
| Package Level 2 Gross Weight | 1125 g |
| Package Level 2 EAN | 8012542585916 |

## Clasificación

| | |
|---|---|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85363010 |
| E-Number (Sweden) | 2100435 |

## Certificados y Declaraciones (Número de Documento)

| | |
|---|---|
| Declaration of Conformity - CE | 9AKK106713A5588 |
| Environmental Information | 2CSC422002K2701 |
| Instructions and Manuals | 9AKK107492A6006 |
| RoHS Information | 2CSC422002K2701 |

## Descargas Populares

| | |
|---|---|
| Data Sheet, Technical Information | 9AKK107492A6187 |
| Instructions and Manuals | 9AKK107492A6006 |

## Clasificaciones

| | |
|---|---|
| Object Classification Code | Q |
| ETIM 6 | EC000905 - Earth leakage circuit breaker |
| ETIM 7 | EC000905 - Earth leakage circuit breaker |

## Categorias

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Interruptores diferenciales → Interruptores diferenciales combinados



