

PRODUCT-DETAILS

# DS201 M C6 A30

## I.com.DS200M 1p+N C 6A A 10kA 30mA



### Información General

Extended Product Type	DS201 M C6 A30
Product ID	2CSR275180R1064
EAN	8012542595410
Catalog Description	I.com.DS200M 1p+N C 6A A 10kA 30mA
Long Description	The DS201 series is a 1P+N RCBO in two-modules width for the protection of end user single-phase circuits against overload and short-circuit currents; protection against the effects of sinusoidal alternating and direct pulsating earth fault currents; protection against indirect contacts and additional protection against direct contacts (with sensitivity = 30 mA).

### Technical

Standards	IEC/EN 61009-1, IEC/EN 61009-2-1
Type of Residual Current	A type
Number of Poles	2
Number of Protected Poles	1
Rated Current ( $I_n$ )	6 A
Rated Current Sensitivity	0.03 A
Rated Voltage ( $U_r$ )	230 V
Rated Insulation Voltage ( $U_i$ )	500 V

Overvoltage Category	III
Pollution Degree	2
Test Voltage (Ut)	170 ... 264 V
Rated Frequency (f)	50 ... 60 Hz
Rated Short-Circuit Capacity ( $I_{cn}$ )	10 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	15 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	11.2 kA
Rated Residual Breaking Capacity ( $I_{\Delta m}$ )	EN 61009-1 6000 A IEC 61009-1 6000 A
Primary Rated Impulse Withstand Voltage	4 kV
Dielectric Test Voltage	2.5 kV
Tripping Characteristic	C
Energy Limiting Class	3
Housing Type	Insulation group I - II, RAL 7035
Actuator Type	Toggle - Insulation group II, Black RAL 9005, sealable in ON-OFF positions
Contact Position Indication	Red ON / Green OFF
Fault Indication	Blue flag on toggle
Electrical Endurance	10000 cycle 20000 cycle
Degree of Protection	Terminals IP20 Housing IP40
Resistance to Shock acc. to IEC 60068-2-27	25g / 2 shocks / 13 ms
Resistance to Vibrations acc. to IEC 60068-2-6	0.1 mm or 1 g - 20 cycles at 5...150...5 Hz
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Reference Ambient Air Temperature	30 °C
Terminal Type	Screw Terminals
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Cable Size	25 mm <sup>2</sup>
Connecting Capacity	Busbar 10/10 mm <sup>2</sup> Stranded 0.75 ... 25 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 16 mm <sup>2</sup> Flexible 0.75 ... 16 mm <sup>2</sup>
Tightening Torque	2.8 N·m
Wire Stripping Length	12 mm
Mounting Type	on DIN rail EN 60715 (35mm) by means of mounting clip
Mounting Position	Any
Power Supply Connection	Arbitrary
Position of Neutral Terminals	Right
Power Loss	2.4 W
Number of Modular	2

## Spacings per DIN Rail

## Accessory Type

Auxiliary contact  
 Signal contact / auxiliary contact  
 Shunt trip  
 Auxiliary contact for bottom fitting  
 Undervoltage release  
 Overvoltage release  
 Motor operating device

---

**Ambiente**

## Ambient Air Temperature

Funcionamiento -25...55 °C

---

**Technical UL/CSA**
Short-Circuit Current  
Rating (SCCR)

0.03 A

---

**Dimensiones**

## Product Net Width

0.035 m

## Product Net Height

0.085 m

Product Net Depth /  
Length

0.069 m

## Product Net Weight

0.200 kg

---

**Información de Embalaje**

## Package Level 1 Units

box 1 piece

## Package Level 1 Width

40 mm

## Package Level 1 Height

106 mm

Package Level 1 Depth /  
Length

80 mm

Package Level 1 Gross  
Weight

225 g

## Package Level 1 EAN

8012542595410

## Package Level 2 Units

5 piece

## Package Level 2 Width

200 mm

## Package Level 2 Height

106 mm

Package Level 2 Depth /  
Length

80 mm

Package Level 2 Gross  
Weight

1125 g

## Package Level 2 EAN

8012542420651

---

**Clasificación**

## Minimum Order Quantity

1 piece

## Customs Tariff Number

85363010

## E-Number (Sweden)

2100496

---

## Certificados y Declaraciones (Número de Documento)

---

Declaration of Conformity - CE	9AKK106713A5588
Environmental Information	2CSC422002K2701
Instructions and Manuals	9AKK107492A6006
RoHS Information	2CSC422002K2701

---

---

## Descargas Populares

---

Data Sheet, Technical Information	9AKK107492A6187
Instructions and Manuals	9AKK107492A6006

---

---

## Clasificaciones

---

Object Classification Code	Q
ETIM 6	EC000905 - Earth leakage circuit breaker
ETIM 7	EC000905 - Earth leakage circuit breaker

---

---

## Categorías

---

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Interruptores diferenciales → Interruptores diferenciales combinados

