PRODUCT-DETAILS

S2C-UA 400 AC

S2C-UA 400 AC - Bobina mínima tensión



Información General

Extended Product Type	S2C-UA 400 AC
Product ID	2CSS200911R0006
EAN	8012542840206
Catalog Description	S2C-UA 400 AC - Bobina mínima tensión
Long Description	The S2C-UA 400 AC undervoltage release has the function to protect the load in case of a voltage drop included between 70% and 35% of its rated value. Positive safety (device tripping when the voltage is disconnected) emergency stop by means of a button. Suitable for MCBs S200 series, RCCBs F200 series and RCBOs DS201, DS202C, DS200 series. It can be used with MCBs SN201 series by means of SN201-IH interface module. Rated voltage: 400V a.c.

Clasificación

EAN	8012542840206
Minimum Order Quantity	1 piece
Customs Tariff Number	85389099

Dimensiones

Product Net Width	18 mm
Product Net Height	0.085 m
Product Net Depth / Length	0.074 m
Product Net Weight	0.090 kg

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Width	0.125 m
Package Level 1 Height	0.035 m
Package Level 1 Depth / Length	0.11 m
Package Level 1 Gross Weight	0.1 kg
Package Level 1 EAN	8012542840206

Ambiente

RoHS Status	Following EU Directive 2011/65/EU

Información Adicional

Number of Switches	1
Power Loss	2.4 W
Product Main Type	S2C-UA
Product Name	Bobina mínima tensión
Rated Voltage (U_r)	400 V
Suitable For	S200, SN201, F200, DS201, DS202C, DS200
Suitable for Product Class	Miniature Circuit Breakers MCBs Residual Current Devices RCDs Residual Current Breakers with Overload Protection RCBo

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	2CSC400002D0209
Declaration of Conformity - CE	9AKK106713A5575
Environmental Information	document not needed
Instructions and Manuals	9AKK107680A3321

Clasificaciones

ETIM 4	EC000042 - Miniature circuit breaker (MCB)
ETIM 5	EC001286 - Auxiliary contact unit for distribution board
ETIM 6	EC001286 - Auxiliary contact unit for distribution board
ETIM 7	EC001286 - Auxiliary device for distribution board devices
Object Classification Code	Q
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Miniature Circuit Breakers MCBs Accessories → Undervoltage Releases

