PRODUCT-DETAILS

E297-16-10/24

Rele de inst. E297-16-10/24 1p 16A 1NA



Información General

Extended Product Type	E297-16-10/24
Product ID	2TAZ311000R2041
EAN	7612270940028
Catalog Description	Rele de inst. E297-16-10/24 1p 16A 1NA
Long Description	Installation relays are electromagnetically operated miniature contactors in the standard DIN width of 18 mm. A reliable control system can be designed using these ABB Installation relays E297. They are used mainly in industrial plants but also in commercial and public buildings. As a rule, installation relays operated by means of a control switch (maintained contact) are installed where it is necessary to operate lighting, an air-conditioning system, a fan or suchlike. Installation relays are also referred to as monostable switching relays or 2-pole miniature contactors. The term "monostable" means that an on command has to be sent to the coil by means of a control switch (maintained operation) in order to excite the magnetic coil. The coil armature attracts and closes or opens the main contacts. The device remains in the on position for as long as the control voltage is applied to the coil. If the voltage flow to the coil is interrupted, the installation relay always returns to the neutral position (off position). Installation relays and the accessories are available in different versions in order to easily satisfy the various market requirements. Their optimal switching capacity also makes them suitable for use in industrial environments and in situations where it is necessary to ensure control over more powerful consumers (such as e.g. multiple lighting ystems). Using an optimized coil (low power loss = lower operating temperature) ensures a clean and safe operation in the electrical distribution board.

Clasificación

E-Number (Sweden)	4001181
EAN	7612270940028
Minimum Order Quantity	10 piece

Customs Tariff Number	85364930

Dimensiones

Product Net Width	18 mm
Product Net Height	85 mm
Product Net Length	62 mm
Product Net Depth / Length	62 mm
Product Net Weight	113 g

Información de Embalaje

Package Level 1 Units	box 10 piece
Package Level 1 Width	96 mm
Package Level 1 Height	82 mm
Package Level 1 Depth / Length	185 mm
Package Level 1 Gross Weight	1206 g
Package Level 1 EAN	7612270940028

Ambiente

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Información Adicional

Connecting Capacity	Solid 1 x 1 ... 10 mm^2 Flexible 2 x 2.5 mm^2 Flexible with Cable End 1 x 0.75 ... 6 mm^2 Flexible with Cable Lug 1 x 0.75 ... 6 mm^2
Frequency (f)	Control Voltage 1 0 ... 50 Hz Control Voltage 2 0 ... 50 Hz
Function	Mechanical
Mounting Type	Din-Rail
Number of Auxiliary Contacts NO	1
Number of Main Contacts NO	1
Options Provided	1NO
Power Loss	0.5 W
Product Main Type	E297
Product Name	Relé de instalación
Rated Control Supply Voltage (U_s)	24 V AC 24 V DC
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Insulation Voltage (U_i)	24 V AC/DC
Rated Operational Voltage	250 V AC
RoHS Date	20170426
Supply Voltage	250...250 V

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	2CCC441020C0201
Declaration of Conformity - CE	2CCC441016D0201
Environmental Information	2CCC441012D0202
Instructions and Manuals	2CCC441006M0801
RoHS Information	2CCC413008D0206

Clasificaciones

ETIM 4	EC001652 - Installation relay
ETIM 5	EC001652 - Installation relay
ETIM 6	EC001652 - Installation relay
ETIM 7	EC001652 - Installation relay
Object Classification Code	K
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Command and Signalling devices → Installation Relays

