ONLINE CERTIFICATIONS DIRECTORY

VPLX.EX15701
Valves, Alarm

Page Bottom

Valves, Alarm

See General Information for Valves, Alarm

AG FIRE SPRINKLER SL EX15701
C/ALFOZ DE BRICIA N 4
POL. IND. VILLALONQUEJAR
09001 BURGOS, SPAIN

Alarm valves, Models "AGE" DN100, DN150, DN200 sizes for horizontal or vertical installation.

Alarm valves, Models H-1, H-2 and H-3 in the 3 and 4 in. sizes for horizontal or vertical installation maximum pressure 300 psig.

Alarm valves, Models H-1, H-2 and H-3 in the 6 in. size for horizontal or vertical installation maximum pressure of 300 psig.

Alarm valves, Models H-1, H-2 and H-3 in the 8 in. size for vertical installation maximum pressure of 300 psig.

Alarm valves, Model H-1 with DIN Class 2633 flange, in the 4 in. size for horizontal or vertical installation.

The above models are intended for use with Models F, WM or WM-2 water motor gongs and Model H Retard Chamber.

Last Updated on 2015-02-09

Questions? Print this page Terms of Use Page Top

© 2016 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2016 UL LLC".