PRODUCT DATASHEET
LS V -500/827/5/IP66

LED STRIP V 500 P | IP66 protected LED strips with 500 lm/m for general applications



Areas of application

- General indoor illumination
- General outdoor illumination
- Decorative illumination
- Private living areas

Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy installation, no tools required for connection
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides
- Suitable for use in damp conditions thanks to high type of protection

Product features

- Flexible and cuttable LED strip
- Smallest cuttable unit: 100 mm
- Lifetime (L70/B50): up to 30,000 h at Tc max.: 75°C
- Luminous flux: 500 lm/m
- Color rendering index R_a: > 80
- Large range of color temperatures: from warm white to cool daylight
- Type of protection: IP65
- Dimmable with suitable drivers, see also www.ledvance.com/dim
- UV restistance (acc. IEC 60068-2-5)
- Salt mist resistance (acc. IEC 60068-2-52)

© 2022, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Electrical data

Nominal wattage	24.00 W
Construction wattage	24.00 W
Nominal wattage per meter	5 W
Nominal voltage	24 V
Type of current	DC
Nominal current	18750 mA

Photometrical data

Luminous efficacy	99 lm/W [1)]
Luminous flux	2185 lm
Luminous flux per meter	495 lm [1)]
Color temperature	2700 K
Color rendering index Ra	> 80
Light color LED	Warm White
Light color (designation)	Warm White
Standard deviation of color matching	≤5 sdcm

1) Value based on first meter of the product


Light technical data

Beam angle	120 °
Rated beam angle (half peak value)	120.00 °

LED MODULE INFORMATION

Number of LEDs per meter	70
Number of LEDs per module	350

Dimensions & Weight



Length	5000.00 mm
Length – smallest unit	100 mm
Cable length	500.000
Width	10.00 mm

© 2022, LEDVANCE GmbH. All rights reserved.

Height	4.10 mm
Conductor cross section	0.5 mm²
LED pitch	14.29 mm
Short pitch	No
Product weight	275.00 g

Temperatures & operating conditions

Ambient temperature range	-20…+55 °C
Maximum temperature at tc test point	75 °C

Lifespan

Nominal lamp life time	30000 h

Capabilities

Dimmable	Yes [1)]
Lowest bending radius	30,0 mm
Self-adhesive	Yes

1) Dimmable with suitable drivers, see also www.ledvance.com/dim

Certificates & Standards

Approval marks – approval	CE / TUV
Protection class	III
Type of protection	IP66
Energy class of contained Light source	F
Salt mist resistance acc. IEC 60068-2-52	Yes
UV resistance acc. IEC 60068-2-5	Yes

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction
PDF	Addon Technical Information
PDF	Declarations of conformity
	IES file (IES)
	LDT file (Eulumdat)

© 2022, LEDVANCE GmbH. All rights reserved.

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075705432	Shipping box 20	550 mm x 325 mm x 270 mm	8353.00 g	48.26 dm^3

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2022, LEDVANCE GmbH. All rights reserved.