PRODUCT-DETAILS

NTU/S12.2000.1

NTU/S12.2000.1 Uninterruptible Power Supply, 12 V DC, 2 A, MDRC



Información General

Extended Product Type	NTU/S12.2000.1
Product ID	2CDG110070R0011
EAN	4016779681179
Catalog Description	NTU/S12.2000.1 Uninterruptible Power Supply, 12 V DC, 2 A, MDRC
Long Description	delivers sufficient power for all types of demanding applications with a buffered output voltage of 12 V DC (SELV) and a maximum output current of 2 A. Operating malfunctions of the power supply are signalled via a changeover contact and can be sent for evaluation purposes. Up to two 12 V DC sealed lead-acid batteries (gel cell) can be connected in parallel with the power supply, in conjunction with the KS/K 4.1 and KS/K 2.1 cable sets, or the AM/S 12.1 battery module.

Clasificación

EAN	4016779681179
Customs Tariff Number	85044090
Minimum Order Quantity	1 piece
E-Number (Switzerland)	405800405
E-Number (Finland)	2815290

Dimensiones

Product Net Depth / Length	64.5 mm
Product Net Height	90 mm
Product Net Width	144 mm

Product Net Weight	0.379 kg

Información de Embalaje

Package Level 1 Units	box 1 piece
Package Level 1 EAN	4016779681179
Package Level 1 Depth / Length	149 mm
Package Level 1 Height	65 mm
Package Level 1 Width	92 mm
Package Level 1 Gross Weight	0.43 kg

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	2CDC501042D0201
Instructions and Manuals	2CDG941059P0003
Declaration of Conformity - CE	2CDK501013D2701
RoHS Information	2CDK501013D2701

Ambiente

RoHS Status	Following EU Directive 2011/65/EU

Clasificaciones

ETIM 5	EC002540 - DC-power supply
ETIM 6	EC002540 - DC-power supply
ETIM 7	EC002540 - DC-power supply
eClass	7.0 27049002
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
IDEA Granular Category Code (IGCC)	4130 >> DC-power supply

Categorias

Productos y sistemas de baja tensión → Home and Building Automation → KNX → Power Supply → Auxiliary Power Supplies

