
PRODUCT-DETAILS

MT/U2.12.2

MT/U2.12.2 Security Terminal, 2-fold, FM



Información General

Extended Product Type	MT/U2.12.2
Product ID	2CDG110111R0011
EAN	4016779711760
Catalog Description	MT/U2.12.2 Security Terminal, 2-fold, FM
Long Description	used for the monitored connection of sensors from security technology (e.g. magnetic contacts or glass-breakage sensors) to the ABB i-bus® KNX. The device has two inputs (" zones") available and can be used as a stand-alone security system or in combination with the security module or intrusion alarm panel with KNX interface. 12 V DC SELV power supply required, e.g. NTU/S 12.2000.1. Typical applications are door and window surveillance, glas-breakage detection as well as area surveillance.

Clasificación

EAN	4016779711760
Customs Tariff Number	85389091
Minimum Order Quantity	1 piece
E-Number (Switzerland)	305960105
E-Number (Finland)	2815321
E-Number (Sweden)	1738039

Dimensiones

Product Net Depth / Length	19 mm
Product Net Height	54.6 mm
Product Net Width	52 mm
Product Net Weight	0.05 kg

Información de Embalaje

Package Level 1 Units	box 1 piece
Package Level 1 EAN	4016779711760
Package Level 1 Depth / Length	23 mm
Package Level 1 Height	65 mm
Package Level 1 Width	92 mm
Package Level 1 Gross Weight	0.08 kg

Certificados y Declaraciones (Número de Documento)

Data Sheet, Technical Information	2CDC513042D0201 2CDC513045D0201
Instructions and Manuals	2CDG941073P0002
Declaration of Conformity - CE	2CDK513012D2701
RoHS Information	2CDK513012D2701

Ambiente


RoHS Status	Following EU Directive 2011/65/EU

Clasificaciones

ETIM 5	EC001100 - Sensor control for bus system
ETIM 6	EC001100 - Sensor control for bus system
ETIM 7	EC001100 - Sensor control for bus system
eClass	7.0 27143130
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Home and Building Automation → KNX → Security - System KNX → Security Modules and Terminals


0 V 8
12 V 7
Out 2 6
Out 1 5
+ 4
0 V 3
+ 2
0 V 1
ABB
ABB i-bus®
MT/U 2.12.2
U_S = 12 V DC
I_S = 0,6 A

