PRODUCT-DETAILS

UD/S6.315.2.1

UD/S6.315.2.1 LED dimmer 6 x 315 W/VA 6/3/2 -gang



Información General

Extended Product Type	UD/S6.315.2.1
Product ID	2CKA006197A0061
EAN	4011395252000
Catalog Description	UD/S6.315.2.1 LED dimmer 6 x 315 W/VA 6/3/2-gang
Long Description	Multichannel universal dimming actuator optimised for dimming retrofit LED lamps (LEDi). Also suitable for dimming incandescent lamps, low-voltage halogen lights with conventional or electronic transformers, 230 V halogen lamps and dimmable energy-saving halogen lamps. Automatic load detection (can be deactivated). Separate N-connection per channel. Parallel connection of the outputs possible to increase the output power. Outputs can be connected in parallel in groups. Minimum load: 2 W. Manual operation on device also possible without bus voltage or in an unprogrammed status. Programming of the device also possible without applied 230V supply voltage. Extensive test and diagnosis functions for the i-Bus tool. Fast parameter setting in ETS using copyable channel templates. With integrated bus coupler. Nominal power at 230 V~ mains voltage: Dimmable 230 V~ LEDi: 6 x 315 W/VA, 2 x 700 W/VA up to 3 x 500 W/VA in trailing edge control, 6 x 120 W/VA, 2 x 250 W/VA up to 3 x 200 W/VA in leading edge control. Inductive L-transformers with LED/low-voltage halogen lamp: 6 x 315 W/VA, 3 x 500 W/VA to 2 x 700 W/VA. Electronic C-transformers with LED/low-voltage halogen lamp: 6 x 315 W/VA, 3 x 500 W/VA to 2 x 700 W/VA. Electronic LC-transformers with LED/low-voltage halogen lamp: 6 x 120 W/VA, 3 x 250 W/VA to 2 x 200 W/VA.

Clasificación

EAN	4011395252000
Customs Tariff Number	85389091
Minimum Order Quantity	1 piece
E-Number (Finland)	2814595

Dimensiones

Product Net Depth / Length	0.064 m
Product Net Height	0.09 m
Product Net Width	0.216 m
Product Net Weight	0.637 kg

Información de Embalaje

Package Level 1 Units	1 piece
Package Level 1 Depth / Length	0.256 m
Package Level 1 Height	0.106 m
Package Level 1 Width	0.125 m
Package Level 1 Gross Weight	766 g

Certificados y Declaraciones (Número de Documento)

Declaration of Conformity - CE	2CKA200000E4777
RoHS Information	9AKK104295D8727

Ambiente

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Clasificaciones

ETIM 6	EC001094 - Dimming actuator for bus system
ETIM 7	EC001094 - Dimming actuator for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categorias

Productos y sistemas de baja tensión → Home and Building Automation → KNX → Lighting Control → Universal Dim Actuators

