



DATOS TÉCNICOS PELLEMATIC MAXI 2 Y MAXI CONDENS

Tipo caldera	CONDENS 					
	PES96	PES112	PES128	PESK110	PESK128	
Potencia nominal/parcial	kW	96-15	112-17	128-19	110-17	128-19
Clase energética		A+	A+	A+	A++	A++
B - Ancho total	mm	2546	2546	2546	-	-
C - Profundidad caldera	mm	1683	1683	1683	-	-
H - Alto total	mm	1680	1680	1680	-	-
H2 - Alto caldera	mm	1562	1562	1562	-	-
T - Profundidad total	mm	1226	1226	1226	-	-
A - Altura conexión ida y retorno	mm	-	-	-	-	-
E - Altura salida de humos	mm	1040	1040	1040	-	-
R - Diámetro salida de humos	mm	250	250	250	-	-
Medida entrada	mm	790	790	790	-	-
Conexión ida y retorno	pulg	2	2	2	-	-
Presión funcionamiento máxima	bar	3	3	3	3	3
Eficiencia potencia nominal	%	92-95	92-95	92-95	102,7	102,7
Eficiencia potencia parcial	%	91-94	91-94	91-94	102	101,9
Contenido agua	l	270	270	270	318	318
Aislamiento térmico 100 mm	W/mK	0,035	0,035	0,035	0,035	0,035
Conexión eléctrica		230VAC / 50Hz / 16A / 1760W				