



DESCRIPTION

**092IHV**

Insulating cases without protection for actuators for **PICV 92 series**. Suggested for heating systems.

Sandwich structure:

- external layer made by high density insulating material to make it hard;
- internal layer made by low density insulating material with high insulation performance.

Made by **2 shells** with **Velcro®**.


MATERIALS

**Body (external layer)**

Polyethylene cross linked foam, density 80 kg/m<sup>3</sup>

**Body (internal layer)**

Polyethylene cross linked foam, density 29 kg/m<sup>3</sup>



TECHNICALS CHARACTERISTICS OF INSULATION

	Standard	Insulation case	
		29	80
Density [Kg/m <sup>3</sup> ]	ISO 845	29	80
Compression stress (50% deflection) [kPa]	ISO 3386/1	88	260
Tensile strength longitudinal [Mpa]	ISO 1798	0.18	0.8
Extension longitudinal stretch [%]	ISO 1798	120 (at break)	170 (at break)
Residual distortion 22 h at 23°C [%] Deflection of 25% 24h after release	ISO 1856	13	1.5
Operating temperature range [°C]	-	-60/+90	-60/+90
Thermal conductivity [W/mK]	EN 12667	0.040	0.049
Fire resistance rating		1 – UNI9177	B2 – DIN4102
UL fire rating	UL94	HF-1	HF-2

Total shell thickness: 20 mm.

DIMENSIONS



Valve size	L	W	H	Weight [g]
92VL ½" / 92L ½"	76	130	118	18
92H ½" / 92L ¾" / 92H ¾"	96	128	102	23
92L 1" / 92H 1"	100	132	132	

Dimensions in mm



DESCRIPTION

**092ICV**

Insulating cases with protection for actuators (thermoelectric and mechanics VA748\_ series) for **PICV 92 series**. Suggested for cooling systems.

Sandwich structure:

- external layer made by high density insulating material to make it hard;
- internal layer made by low density insulating material with high insulation performance.

Made by **2 shells** with **Velcro®**.


MATERIALS

*Body (external layer)*

Polyethylene cross linked foam, density 80 kg/m<sup>3</sup>

*Body (internal layer)*

Polyethylene cross linked foam, density 29 kg/m<sup>3</sup>



TECHNICALS CHARACTERISTICS OF INSULATION

	Standard	Insulation case	
		29	80
Density [Kg/m <sup>3</sup> ]	ISO 845	29	80
Compression stress (50% deflection) [kPa]	ISO 3386/1	88	260
Tensile strength longitudinal [Mpa]	ISO 1798	0.18	0.8
Extension longitudinal stretch [%]	ISO 1798	120 (at break)	170 (at break)
Residual distortion 22 h at 23°C [%] <small>Deflection of 25% 24h after release</small>	ISO 1856	13	1.5
Operating temperature range [°C]	-	-60/+90	-60/+90
Thermal conductivity [W/mK]	EN 12667	0.040	0.049
Fire resistance rating		1 – UNI9177	B2 – DIN4102
UL fire rating	UL94	HF-1	HF-2

Total shell thickness: 20 mm.

DIMENSIONS



Valve size	L	W	H	Weight [g]
92VL ½" / 92L ½"	76	130	201	38
92H ½" / 92L ¾" / 92H ¾"	96	128	206	42

Dimensions in mm