

1. Specification

LSP Duct

Model Name	Indoor Unit			AC026RNLDKG/EU	AC035RNLDKG/EU
	Outdoor Unit			AC026RXADKG/EU	AC035RXADKG/EU
Mode				-	HEAT PUMP
Performance	Capacity (Min/Std/Max)	Cooling	kW	0.80 / 2.60 / 3.80	0.85 / 3.50 / 4.30
			Btu/h	2,730 / 8,870 / 12,970	2,900 / 11,940 / 14,670
		Heating	kW	0.98 / 3.30 / 4.30	1.00 / 4.00 / 5.00
			Btu/h	3,340 / 11,260 / 14,670	3,410 / 13,650 / 17,060
Power	Power Input (Min/Std/Max)	Cooling	kW	0.19 / 0.68 / 1.20	0.20 / 1.12 / 1.40
		Heating	kW	0.20 / 0.87 / 1.45	0.19 / 1.21 / 1.80
	Current Input (Min/Std/Max)	Cooling	A	1.5 / 3.6 / 5.5	1.6 / 5.4 / 6.5
		Heating	A	1.3 / 4.5 / 7.0	1.3 / 5.8 / 10.5
	Current	MCA	A	11.7	11.7
		MFA	A	12.9	12.9
Efficiency	EER	Cooling	-	3.82	3.12
	COP	Heating	-	3.79	3.31
	SEER (Cooling Energy Grade)		-	6.2 (A++)	6.1 (A++)
	SCOP (Heating Energy Grade)		-	4.0 (A+)	4.0 (A+)
	Pdesignh		kW	2.0	2.0
Piping Connections	Liquid Pipe	Type		Flare connection	Flare connection
		Φ, mm (inch)		6.35 (1/4)	6.35 (1/4)
	Gas Pipe	Type		Flare connection	Flare connection
		Φ, mm (inch)		9.52 (3/8)	9.52 (3/8)
	Heat Insulation		-	Both liquid and gas pipes	Both liquid and gas pipes
	Piping length (ODU-IDU)	Standard	m	5	5
		Max.	m	20	20
Elevation		m	15	15	
Chargeless		m	20	20	
Wiring connections	Communication	Min.	mm ²	0.75	0.75
		Remark	-	F1, F2	F1, F2
Refrigerant	Type		-	R32	R32
	Factory Charging	kg	0.9	0.9	
		tCO ₂ e	0.61	0.61	

1. Specification

LSP Duct

Model Name	Indoor Unit		AC026RNLDKG/EU	AC035RNLDKG/EU
	Outdoor Unit		AC026RXADKG/EU	AC035RXADKG/EU
Power Supply			Ø, #, V, Hz	1,2,220-240,50
Heat Exchanger	Type		-	F&T
	Material	Fin	-	Al
		Tube	-	Cu
	Fin Treatment		-	Green Hydrophile
Fan	Type		-	Sirocco
	Quantity		EA	2
	Air Flow Rate	Cooling (H/M/L)	m ³ /min	9.0 / 8.2 / 7.4
			l/s	150 / 136.6 / 123.3
		Heating (H/M/L)	m ³ /min	10.0 / 9.0 / 8.0
			l/s	166.6 / 150 / 133.3
External Static Pressure	Min/Std/Max	mmAq	0/2.5/4	
		Pa	0/25/39	
Fan Motor	Type		-	BLDC
	Output		W x n	153 x 1
Drain	Drain Pipe		Φ, mm	VP-25(OD32, ID25)
Sound	Sound Pressure Level	High/Mid/Low/(Silent)	dB(A)	32 / 29 / 26
	Sound Power Level		dB(A)	53
External Dimension	Net Weight		kg	19.0
	Shipping Weight		kg	23.0
	Net Dimensions (WxHxD)		mm	700 x 199 x 600
	Shipping Dimensions (WxHxD)		mm	951 x 280 x 709
Casing	Material		-	EGI Steel Plate
	Infrared remote control		-	AR-EH03E
Control System	Wired remote control		-	MWR-WE13N MWR-WG00*N
	Drain Pump	Drain Pump		-
Max. lifting Height / Displacement		mm / Liter / h	-	
Additional Accessories	Drain Pump	External Model	-	-
		Internal Model	-	MDP-E075SEE3D
	Max. lifting Height / Displacement		mm / Liter / h	750/24
	Air Filter		-	Removable / Washable
Virus Doctor		-	-	

1. Specification

LSP Duct

	Model Name			AC026RNLDKG/EU	AC035RNLDKG/EU	
	Indoor Unit			AC026RXADKG/EU	AC035RXADKG/EU	
Outdoor Unit	Power Supply		Ø, #, V, Hz	1, 2, 220-240, 50	1, 2, 220-240, 50	
	Heat Exchanger	Type		-	Fin & Tube	Fin & Tube
		Material	Fin	-	Al	Al
			Tube	-	Cu	Cu
	Fin Treatment		-	Anti-Corrosion	Anti-Corrosion	
	Compressor	Model Name			UB9AK5090FER	UB9AK5090FER
		Type		-	Single BLDC	Single BLDC
		Output		kW	0.86	0.86
		Oil	Type	-	POE	POE
	Initial charge		cc	320	320	
	Fan	Type		-	Propeller	Propeller
		Discharge direction		-	Front	Front
		Quantity		EA	1	1
		Air Flow Rate			m ³ /min	30
			l/s	500	500	
	Fan Motor	Type		-	BLDC Motor	BLDC Motor
		Output		W x n	40 x 1	40 x 1
	Sound	Sound Pressure Level	Cooling	dB(A)	46	48
			Heating	dB(A)	47	48
		Sound Power Level		dB(A)	59	61
External Dimension	Net Weight		kg	32.5	32.5	
	Shipping Weight		kg	35.5	35.5	
	Net Dimensions (WxHxD)		mm	790 x 548 x 285	790 x 548 x 285	
	Shipping Dimensions (WxHxD)		mm	913 x 622 x 371	913 x 622 x 371	
Casing	Material	Body	-	EGI Steel Plate	EGI Steel Plate	
	Operating Temp. Range	Cooling	°C	-15 ~ 46	-15 ~ 46	
Heating		°C	-20 ~ 24	-20 ~ 24		

NOTE

- Specification may be subject to change without prior notice.
 - 1) Performances are based on the following test conditions.
 - Cooling : Indoor temperature 27°C DB, 19°C WB, Outdoor temperature 35°C DB, 24°C WB
 - Heating : Indoor temperature 20°C DB, 15°C WB, Outdoor temperature 7°C DB, 6°C WB
 - Equivalent refrigerant pipe length 5m, Level differences 0m
 - 2) Select wire size based on the value of MCA
 - 3) Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
 - 4) Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
 - 5) These products contain R32(GWP=675) which is fluorinated greenhouse gas.
 - 6) 'MWR-WG00*N' is new wired remote control type(Graphic).
If you need the latest control system information, please refer to SAC control TDB.