

1. Specification

Big Ceiling

System	Model Name		Indoor Unit	AC100RNCDKG/EU	AC100RNCDKG/EU	AC120RNCDKG/EU		
			Outdoor Unit	AC100RXADKG/EU	AC100RXADNG/EU	AC120RXADKG/EU		
	Mode			-	HEAT PUMP	HEAT PUMP	HEAT PUMP	
	Performance	Capacity (Min/Std/Max)	Cooling	kW	3.0 / 10.0 / 12.0	3.0 / 10.0 / 12.0	3.0 / 12.0 / 13.5	
				Btu/h	10,240 / 34,120 / 41,000	10,240 / 34,120 / 41,000	10,240 / 41,000 / 46,100	
			Heating	kW	2.2 / 11.2 / 15.5	2.2 / 11.2 / 15.5	3.8 / 13.2 / 16.5	
				Btu/h	7,500 / 38,210 / 52,900	7,500 / 38,210 / 52,900	12,970 / 45,040 / 56,300	
	Power	Power Input (Min/Std/Max)	Cooling	kW	0.60 / 3.28 / 4.70	0.60 / 3.15 / 4.70	0.90 / 4.35 / 5.30	
			Heating	kW	0.46 / 3.25 / 5.40	0.46 / 3.20 / 5.40	0.70 / 3.83 / 5.60	
		Current Input (Min/Std/Max)	Cooling	A	3.0 / 14.6 / 20.4	1.5 / 5.0 / 7.1	5.1 / 19.1 / 24.0	
			Heating	A	2.5 / 14.2 / 23.0	1.2 / 5.1 / 8.4	3.9 / 17.0 / 26.0	
		Current	MCA	A	26.5	18.6	26.5	
			MFA	A	30.0	18.6	30.0	
	Efficiency	EER	Cooling	-	3.05	3.17	2.76	
		COP	Heating	-	3.44	3.50	3.44	
		SEER (Cooling Energy Grade)		-	6.1 (A++)	6.1 (A++)	5.9 (A+)	
		SCOP (Heating Energy Grade)		-	4.0 (A+)	4.0 (A+)	4.0 (A+)	
		Pdesignh		kW	5.2	5.2	6.5	
	Piping Connections	Liquid Pipe		Type	Flare connection	Flare connection	Flare connection	
				Φ, mm (inch)	9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	
		Gas Pipe		Type	Flare connection	Flare connection	Flare connection	
				Φ, mm (inch)	15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	
		Heat Insulation		-	Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes	
		Piping length (ODU-IDU)	Standard	Max.	m	5	5	5
				Elevation	m	30	30	30
				Chargeless	Min.	mm ²	0.75	0.75
	Remark				-	F1, F2	F1, F2	F1, F2
	Wiring connections	Communication		-	R32	R32	R32	
Factory Charging		kg	2.7	2.7	2.7			
			tCO ₂ e	1.82	1.82	1.82		

1. Specification

Big Ceiling

Model Name	Indoor Unit		AC100RNCDKG/EU	AC100RNCDKG/EU	AC120RNCDKG/EU	
	Outdoor Unit		AC100RXADKG/EU	AC100RXADNG/EU	AC120RXADKG/EU	
Power Supply			Ø, #, V, Hz	1,2,220-240,50	1,2,220-240,50	1,2,220-240,50
Heat Exchanger	Type		-	F&T	F&T	F&T
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile	
Fan	Type		-	Sirocco	Sirocco	Sirocco
	Quantity		EA	4	4	4
	Air Flow Rate	Cooling (H/M/L)	m ³ /min	26.0 / 23.0 / 19.0	26.0 / 23.0 / 19.0	30.0 / 24.0 / 20.0
		Heating (H/M/L)	l/s	433 / 383 / 317	433 / 383 / 317	500 / 400 / 333
Fan Motor	Type		-	BLDC	BLDC	BLDC
	Output		W x n	244 x 1	244 x 1	244 x 1
Drain	Drain Pipe		Φ, mm	VP-25(OD32, ID25)	VP-25(OD32, ID25)	VP-25(OD32, ID25)
Sound	Sound Pressure Level	High/Mid/Low/(Silent)	dB(A)	42 / 38 / 34	42 / 38 / 34	44 / 41 / 37
	Sound Power Level		dB(A)	60	60	62
External Dimension	Net Weight		kg	42.0	42.0	42.0
	Shipping Weight		kg	48.0	48.0	48.0
	Net Dimensions (WxHxD)		mm	1,650 x 235 x 675	1,650 x 235 x 675	1,650 x 235 x 675
	Shipping Dimensions (WxHxD)		mm	1,739 x 321 x 758	1,739 x 321 x 758	1,739 x 321 x 758
Casing	Material		-	GI Steel Plate	GI Steel Plate	GI Steel Plate
Control System	Infrared remote control		-	AR-EH03E	AR-EH03E	AR-EH03E
	Wired remote control		-	MWR-WE13N MWR-WG00*N	MWR-WE13N MWR-WG00*N	MWR-WE13N MWR-WG00*N
Drain Pump	Drain Pump		-	-	-	-
	Max. lifting Height / Displacement		mm / Liter / h	-	-	-
Additional Accessories	Drain Pump	External Model	-	-	-	-
		Internal Model	-	-	-	-
	Max. lifting Height / Displacement	mm / Liter / h	-	-	-	-
		Air Filter		-	Removable / Washable	Removable / Washable
Virus Doctor		-	Option	Option	Option	

1. Specification

Big Ceiling

Model Name	Indoor Unit			AC100RNCDKG/EU	AC100RNCDKG/EU	AC120RNCDKG/EU
	Outdoor Unit			AC100RXADKG/EU	AC100RXADNG/EU	AC120RXADKG/EU
Power Supply	Ø, #, V, Hz			1, 2, 220-240, 50	3, 4, 380-415, 50	1, 2, 220-240, 50
Heat Exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
Fin Treatment		-	Anti-Corrosion	Anti-Corrosion	Anti-Corrosion	
Compressor	Model Name			UB8TN8300FJU	UB8TN8300FJU	UB5TN5450FJX
	Type			Twin BLDC	Twin BLDC	Twin BLDC
	Output		kW	2.91	2.91	4.25
	Oil	Type	-	POE	POE	POE
Initial charge		cc	1,200	1,200	1,700	
Fan	Type		-	Propeller	Propeller	Propeller
	Discharge direction		-	Front	Front	Front
	Quantity		EA	1	1	1
	Air Flow Rate		m ³ /min	72	72	72
l/s			1,200	1,200	1,200	
Fan Motor	Type			BLDC Motor	BLDC Motor	BLDC Motor
	Output		W x n	125 x 1	125 x 1	125 x 1
Sound	Sound Pressure Level	Cooling	dB(A)	52	52	54
		Heating	dB(A)	54	54	56
	Sound Power Level		dB(A)	69	69	70
External Dimension	Net Weight		kg	75.0	74.0	81.0
	Shipping Weight		kg	80.0	79.0	86.0
	Net Dimensions (WxHxD)		mm	940 x 998 x 330	940 x 998 x 330	940 x 998 x 330
	Shipping Dimensions (WxHxD)		mm	995 x 1,096 x 426	995 x 1,096 x 426	995 x 1,096 x 426
Casing	Material	Body	-	EGI Steel Plate	EGI Steel Plate	EGI Steel Plate
		Operating Temp. Range			°C	-15 ~ 50
Cooling		°C	-20 ~ 24	-20 ~ 24	-20 ~ 24	
Heating		°C	-20 ~ 24	-20 ~ 24	-20 ~ 24	

NOTE

- Specification may be subject to change without prior notice.
 - 1) Performances are based on the following test conditions.
 - Cooling : Indoor temperature 27°C DB, 19°C WB, Outdoor temperature 35°C DB, 24°C WB
 - Heating : Indoor temperature 20°C DB, 15°C WB, Outdoor temperature 7°C DB, 6°C WB
 - Equivalent refrigerant pipe length 5m, Level differences 0m
 - 2) Select wire size based on the value of MCA
 - 3) Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
 - 4) Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
 - 5) These products contain R32(GWP=675) which is fluorinated greenhouse gas.
 - 6) 'MWR-WG00*N' is new wired remote control type(Graphic).
If you need the latest control system information, please refer to SAC control TDB.