

1. Specification

MSP Duct

Model Name	Indoor Unit			AC100RNMDKG/EU	AC100RNMDKG/EU	AC120RNMDKG/EU	
	Outdoor Unit			AC100RXADKG/EU	AC100RXADNG/EU	AC120RXADKG/EU	
Mode				-	HEAT PUMP	HEAT PUMP	HEAT PUMP
Performance	Capacity (Min/Std/Max)	Cooling	kW	3.0 / 10.0 / 12.0	3.0 / 10.0 / 12.0	3.0 / 12.0 / 13.5	
			Btu/h	10,240 / 34,120 / 41,000	10,240 / 34,120 / 41,000	10,240 / 41,000 / 46,100	
		Heating	kW	2.2 / 11.2 / 15.5	2.2 / 11.2 / 15.5	2.5 / 13.2 / 17.0	
			Btu/h	7,500 / 38,210 / 52,900	7,500 / 38,210 / 52,900	8,530 / 45,040 / 58,000	
Power	Power Input (Min/Std/Max)	Cooling	kW	0.60 / 3.44 / 4.70	0.60 / 3.42 / 4.70	0.90 / 4.50 / 5.30	
		Heating	kW	0.46 / 3.50 / 5.40	0.46 / 3.42 / 5.40	0.70 / 3.86 / 5.60	
	Current Input (Min/Std/Max)	Cooling	A	3.0 / 15.2 / 20.4	1.5 / 5.3 / 7.1	5.0 / 19.7 / 24.0	
		Heating	A	2.5 / 15.4 / 23.0	1.2 / 5.3 / 8.4	4.0 / 17.1 / 26.0	
	Current	MCA	A	26.5	18.6	26.5	
		MFA	A	30.0	18.6	30.0	
Efficiency	EER	Cooling	-	2.90	2.92	2.66	
	COP	Heating	-	3.20	3.27	3.42	
	SEER (Cooling Energy Grade)		-	5.9 (A+)	5.9 (A+)	5.8 (A+)	
	SCOP (Heating Energy Grade)		-	4.0 (A+)	4.0 (A+)	4.0 (A+)	
	Pdesignh		kW	5.2	5.2	6.5	
Piping Connections	Liquid Pipe	Type		Flare connection	Flare connection	Flare connection	
		Φ, mm (inch)		9.52 (3/8)	9.52 (3/8)	9.52 (3/8)	
	Gas Pipe	Type		Flare connection	Flare connection	Flare connection	
		Φ, mm (inch)		15.88 (5/8)	15.88 (5/8)	15.88 (5/8)	
	Heat Insulation		-	Both liquid and gas pipes	Both liquid and gas pipes	Both liquid and gas pipes	
	Piping length (ODU-IDU)	Standard	m	5	5	5	
		Max.	m	50	50	50	
Elevation		m	30	30	30		
Chargeless		m	30	30	30		
Wiring connections	Communication	Min.	mm ²	0.75	0.75	0.75	
		Remark	-	F1, F2	F1, F2	F1, F2	
Refrigerant	Type		-	R32	R32	R32	
	Factory Charging		kg	2.7	2.7	2.7	
			tCO ₂ e	1.82	1.82	1.82	

1. Specification

MSP Duct

Model Name	Indoor Unit			AC100RNMDKG/EU	AC100RNMDKG/EU	AC120RNMDKG/EU
	Outdoor Unit			AC100RXADKG/EU	AC100RXADNG/EU	AC120RXADKG/EU
Power Supply			Ø, #, V, Hz	1,2,220-240,50	1,2,220-240,50	1,2,220-240,50
Heat Exchanger	Type		-	F&T	F&T	F&T
	Material	Fin	-	Al	Al	Al
		Tube	-	Cu	Cu	Cu
Fin Treatment		-	Green Hydrophile	Green Hydrophile	Green Hydrophile	
Fan	Type		-	Sirocco	Sirocco	Sirocco
	Quantity		EA	3	3	3
	Air Flow Rate	Cooling (H/M/L)	m ³ /min	28.0 / 25.0 / 22.0	28.0 / 25.0 / 22.0	33.0 / 28.0 / 23.0
			l/s	467 / 417 / 367	467 / 417 / 367	550 / 467 / 383
	Air Flow Rate	Heating (H/M/L)	m ³ /min	28.0 / 25.0 / 22.0	28.0 / 25.0 / 22.0	33.0 / 28.0 / 23.0
l/s			467 / 417 / 367	467 / 417 / 367	550 / 467 / 383	
External Static Pressure	Min/Std/Max	mmAq	0.0 / 4.0 / 15.0	0.0 / 4.0 / 15.0	0.0 / 5.2 / 15.0	
		Pa	0.0 / 39.2 / 147.0	0.0 / 39.2 / 147.0	0.0 / 51.0 / 147.0	
Fan Motor	Type		-	BLDC	BLDC	BLDC
	Output		W x n	153 x 1	153 x 1	244 x 1
Drain	Drain Pipe		Φ, mm	VP-25(OD32, ID25)	VP-25(OD32, ID25)	VP-25(OD32, ID25)
Sound	Sound Pressure Level	High/Mid/Low/(Silent)	dB(A)	34 / 32 / 30	34 / 32 / 30	37 / 34 / 30
	Sound Power Level		dB(A)	58	58	62
External Dimension	Net Weight		kg	34.0	34.0	38.5
	Shipping Weight		kg	39.0	39.0	45.0
	Net Dimensions (WxHxD)		mm	1,200 x 250 x 700	1,200 x 250 x 700	1,300 x 300 x 700
	Shipping Dimensions (WxHxD)		mm	1,429 x 320 x 779	1,429 x 320 x 779	1,529 x 370 x 779
Casing	Material		-	GI Steel Plate	GI Steel Plate	GI Steel Plate
Control System	Infrared remote control		-	AR-EH03E	AR-EH03E	AR-EH03E
	Wired remote control		-	MWR-WE13N MWR-WG00*N	MWR-WE13N MWR-WG00*N	MWR-WE13N MWR-WG00*N
Drain Pump	Drain Pump		-	-	-	-
	Max. lifting Height / Displacement		mm / Liter / h	-	-	-
Additional Accessories	Drain Pump	External Model	-	MDP-G075SP	MDP-G075SP	MDP-G075SP
		Internal Model	-	MDP-G075SQ	MDP-G075SQ	MDP-G075SQ
		Max. lifting Height / Displacement	mm / Liter / h	750 / 24	750 / 24	750 / 24
	Air Filter		-	Removable / Washable	Removable / Washable	Removable / Washable
	Virus Doctor		-	Option	Option	Option

1. Specification

MSP Duct

	Model Name		Indoor Unit	AC100RNMDKG/EU	AC100RNMDKG/EU	AC120RNMDKG/EU	
			Outdoor Unit	AC100RXADKG/EU	AC100RXADNG/EU	AC120RXADKG/EU	
Outdoor Unit	Power Supply		Ø, #, V, Hz	1, 2, 220-240, 50	3, 4, 380-415, 50	1, 2, 220-240, 50	
	Heat Exchanger	Type		-	Fin & Tube	Fin & Tube	Fin & Tube
		Material	Fin	-	Al	Al	Al
			Tube	-	Cu	Cu	Cu
		Fin Treatment		-	Anti-Corrosion	Anti-Corrosion	Anti-Corrosion
	Compressor	Model Name			UB8TN8300FJU	UB8TN8300FJU	UB5TN5450FJX
		Type		-	Twin BLDC	Twin BLDC	Twin BLDC
		Output		kW	2.91	2.91	4.25
		Oil	Type	-	POE	POE	POE
	Initial charge		cc	1,200	1,200	1,700	
	Fan	Type		-	Propeller	Propeller	Propeller
		Discharge direction		-	Front	Front	Front
		Quantity		EA	1	1	1
		Air Flow Rate	m ³ /min			72	72
	l/s			1,200	1,200	1,200	
	Fan Motor	Type		-	BLDC Motor	BLDC Motor	BLDC Motor
		Output		W x n	125 x 1	125 x 1	125 x 1
	Sound	Sound Pressure Level	Cooling	dB(A)	52	52	54
			Heating	dB(A)	54	54	56
		Sound Power Level		dB(A)	69	69	70
External Dimension	Net Weight		kg	75.0	74.0	81.0	
	Shipping Weight		kg	80.0	79.0	86.0	
	Net Dimensions (WxHxD)		mm	940 x 998 x 330	940 x 998 x 330	940 x 998 x 330	
	Shipping Dimensions (WxHxD)		mm	995 x 1,096 x 426	995 x 1,096 x 426	995 x 1,096 x 426	
Casing	Material	Body	-	EGI Steel Plate	EGI Steel Plate	EGI Steel Plate	
	Operating Temp. Range	Cooling	°C	-15 ~ 50	-15 ~ 50	-15 ~ 50	
Heating		°C		-20 ~ 24	-20 ~ 24	-20 ~ 24	

NOTE

- Specification may be subject to change without prior notice.
 - 1) Performances are based on the following test conditions.
 - Cooling : Indoor temperature 27°C DB, 19°C WB, Outdoor temperature 35°C DB, 24°C WB
 - Heating : Indoor temperature 20°C DB, 15°C WB, Outdoor temperature 7°C DB, 6°C WB
 - Equivalent refrigerant pipe length 5m, Level differences 0m
 - 2) Select wire size based on the value of MCA
 - 3) Sound pressure level is obtained in an anechoic room.
 - Sound pressure level is a relative value, depending on the distance and acoustic environment.
 - Sound pressure level may differ depending on operation condition.
 - dBA = A-weighted sound pressure level
 - Reference acoustic pressure 0 dB = 20uPa
 - 4) Sound power level is an absolute value that a sound source generates.
 - dBA = A-weighted sound power level
 - Reference power : 1pW
 - Measured according to ISO 3741
 - 5) These products contain R32(GWP=675) which is fluorinated greenhouse gas.
 - 6) 'MWR-WG00*N' is new wired remote control type(Graphic).
If you need the latest control system information, please refer to SAC control TDB.