






IKUSI
velatia

smartexperience

Distribuidores de interior serie UDF

Elementos de distribución idóneos para instalaciones ICT



Distribuidores con paso de corriente entre todas las salidas y la entrada

MODELO			UDF-205	UDF-307	UDF-408	UDF-612	UDF-813
REF.			2075	2076	2077	2078	2079
Número de salidas			2	3	4	6	8
Atenuación de distribución	5-862 MHz	dB	≤ 3,6	≤ 6,8	≤ 8,1	≤ 11,8	≤ 11,9
	950-1550 MHz		≤ 4,1	≤ 8,5	≤ 9,1	≤ 13,5	≤ 14,1
	1551-2150 MHz		≤ 4,5	≤ 9,7	≤ 10,4	≤ 15,1	≤ 15,8
	2151-2400 MHz		≤ 6	≤ 10,1	≤ 11	≤ 15,1	≤ 17
Desacoplo entre salidas	5-300 MHz	dB	≥ 35	≥ 25	≥ 24	≥ 28	≥ 26
	301-862 MHz		≥ 34	≥ 25	≥ 22	≥ 25	≥ 28
	950-2400 MHz		≥ 20	≥ 21	≥ 22	≥ 25	≥ 28

Distribuidores UDF



Pº Miramón, 170
20014 San Sebastián - SPAIN
Tel.: +34 943 44 88 00 - Fax: +34 943 44 88 20
television@ikusi.com - www.ikusi.tv