

UPM 1400 Combi meter

Art. Number 304579



Technical Specifications

ORDER INFORMATION

EAN Number 5702663045798

CHARACTERISTICS

Audio decoding MPEG-2 layer I and II (Music cam), MPEG4, AAC, Dolby Digital (AC-3)

Video decoding MPEG1, MPEG-2 MP@ML, H.264, VC1, DV, MPEG-4, H.265 (1080p@60fps)

FREQUENCY RANGE

Measurement Range Combo COFDM, QAM & QPSK

Measurement Range A DVB-S/S2

Measurement Range B DVB-T/T2

Measurement Range C DVB-C

Measurement Range D H.265/HEVC & MPEG4

Frequency range | MHz 50...2150 MHz

Measurement sensitivity VHF/UHF | dB μ V 35...105 dB μ V

Measurement sensitivity SAT | dB μ V 35...95 dB μ V

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL

Remote voltage - DVB-T/SAT DVB-T 5V, 12-24V / DVB-S 13V, 18V, LNB Test 12V-20V

Battery type Li-Ion

AC Supply voltage | VAC 100-240 VAC

DC Operating voltage | VDC 15 VDC

PSU/adapter INFO Included Euro Plug (CEE 7/17)



Technical Specifications

PSU/adapter Art number 304527

CONNECTORS

Connector IN F-female

Connector USB 1

Connector LAN 1

MECHANICAL

Display TFT 5 inch color

Dimensions product (H x D x W) | mm 145 x 220 x 50 mm

Packing QTY 1

Packaging Height | m 0.125 m

Packaging Width | m 0.282 m

Packaging Depth | m 0.185 m

Packaging Volume | m3 0.007 m3

Net Weight | kg 0.850 kg

Tara Weight | kg 0.050 kg

Total Weight | kg 0.900 kg