

TRIAX TR 65, DVB-T2 HEVC, FTA

Art. Number 305265



The TR 65 is a DVB-T2 HEVC/H.265 Set Top Box with a 4 digits display to be used in any country where DVB-T1, DVB-T2, MPEG4 or HEVC FTA signals are broadcasted.

Technical Specifications

ORDER INFORMATION

EAN Number 5702663052659

CHARACTERISTICS

TER - demodulation	DVB-T/T2 (MPEG2/MPEG4/HEVC - H265)
TER - signal level dBm	-70...-15 dBm
Aspect ratio	4:3 / 16:9 / Auto
Video decoding	MPEG2 MP@HL, AVC/H.264 HP@L4.1, MPEG4 ASP, HEVC H 265
Video output	576i, 576p, 720p, 1080i, 1080p
HDMI Version	1.3
Digital audio output (S/PDIF)	1 x Coaxial
Video playback format	AVI, FLV, MKV, TS, M2TS, M2T,MTS,TRP, TP, MPG, MPEG, MP4, MOV, WEBM, VOB
Photo playback format	BMP, JPG, JPEG
Audio playback format	MP1,MP2, MP3, AAC, AC3

FREQUENCY RANGE

TER - frequency range MHz	170...230, 470...862 MHz
TER - channel bandwidth MHz	7...8 MHz
Sampling frequency kHz	32, 44.1, 48 kHz
Number of channels	1000

ELECTRICAL



Technical Specifications

Impedance Ω	75 Ω
OPERATIONAL	
Active Antenna V/mA	5/50 V/mA
Ethernet Interface	10/100 Mbps
Flash memory MByte	32 MByte
DDR memory MByte	512 MByte
OSD languages	9
Functions	Mediaplayer, PVR and Software update
API	Web radios, weather forecasts
Decryption	FTA
PVR ready	Yes (USB)
Remote control	Included
Remote control - keys	45
Replacement Remote art. no	351130, item TCT 043
Battery type	2 x AAA
Software update	via USB
AC Supply voltage VAC	100-240 VAC
Power Consumption (typ.) W	6 ON / 0.5 STBY W
User guide	French
Temperature - operating $^{\circ}\text{C}$	5...35 $^{\circ}\text{C}$

CONNECTORS

USB port	USB on the front
TER - input connector	IEC female
Connector Optical out	S/PDIF Coax
Connector HDMI	HDMI female (Type A)
Connector SCART	SCART in/out
Connector TER in	IEC-female

MECHANICAL

Display	4-Digit,
Display segments	4 x 7 segment
Display colour	Green
Main material	Steel
Finish	Black Matte
Colour	Black
Packing QTY	1
Product Height mm	36 mm
Product Width mm	168 mm
Product Depth mm	110 mm
Packaging Height m	0.038 m
Packaging Width m	0.168 m



TRIAX

connecting the future

Technical Specifications

Packaging Depth m	0.118 m
Packaging Volume m ³	0.001 m ³
Net Weight kg	0.350 kg
Tara Weight kg	0.000 kg
Total Weight kg	0.350 kg