

Potencia (Composición) kvar (440V)		Potencia kvar (400V)	Dimensiones H x A x B mm	Peso Kg	Tipo	Calibre int. A
440V, 50Hz						
12	3+3+6	10	500x400x200	14	PROSEC 12	63
15	3+6+6	12,5	500x400x200	14	PROSEC 15	63
17,5	2,5+5+10	14,5	500x400x200	14	PROSEC 17	63
21	3+6+12	17,5	500x400x200	14	PROSEC 21	63
22,5	2,5+10+10	18,2	500x400x200	14	PROSEC 22	63
24	6+6+12	20	500x400x200	14	PROSEC 24	63
25	5+2x10	20,7	500x400x200	14	PROSEC 25	63
27	3+12+12	23,0	500x400x200	14	PROSEC 27	63
30	5+12,5+12,5	25	500x400x200	14	PROSEC 30	63
36	6+15+15	30	600x500x250	19	PROSEC 36	125
39	3+12+24	32,5	600x500x250	20	PROSEC 39	125
42	6+12+24	35	600x500x250	20	PROSEC 42	125
45	3+6+12+24	37,5	600x500x250	20	PROSEC 45	125
50	10+2x20	41,3	600x500x250	20	PROSEC 50	125
54	6+12+12+24	45	600x500x250	20	PROSEC 54	125
60	6+15+15+24	50	600x500x250	20	PROSEC 60	125
63	3+12+24+24	52,5	600x500x250	20	PROSEC 63	125
66	6+12+24+24	55	600x500x250	20	PROSEC 66	125
69	3+12+24+30	57,5	800x600x300	26	PROSEC 69	160
78	12+12+24+30	65	800x600x300	26	PROSEC 78	160
87	3+12+24+24+24	72,5	800x600x300	28	PROSEC 87	160
90	15+15+30+30	75	800x600x300	28	PROSEC 90	160
92,5	5+12,5+25+25+25	76,4	800x600x300	28	PROSEC 92	250
96	12+24+30+30	80	800x600x300	28	PROSEC 96	250
108	3+15+30+30+30	90	800x600x300	30	PROSEC 108	250
112,5	6+15+30+30+30	93	800x600x300	30	PROSEC 112	250
114	15+15+24+30+30	95	800x600x300	32	PROSEC 114	250
120	15+15+30+30+30	100	800x600x300	32	PROSEC 120	250