



Datos técnicos Gama CV-M1B / MVV-SB



Acumulador gama CV-RB.



Acumulador gama MVV-RB.

Tipos		CV 1500-RB	MVV 2000-RB	MVV 2500-RB	MVV 3000-RB	MVV 3500-RB	MVV 4000-RB	MVV 5000-RB
Capacidad a.c.s	►[l]	1500	2000	2500	3000	3500	4000	5000
Peso en vacío (aprox.)	►[kg]	343	460	635	705	755	915	1030
kW: Entrada agua fría	►[“GAS/m]	1 1/2	2	3	3	3	3	3
e: Desagüe	►[“GAS/m]	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2
ww: Salida de a.c.s.	►[“GAS/m]	1 1/2	2	3	3	3	3	3
z: Recirculación	►[“GAS/m]	1 1/2	1 1/2	2	2	2	2	2
eh: Conexión lateral	►[“GAS/m]	2	2	2	2	2	2	2
R: Conexión lateral	►[“GAS/m]	2	2	2	2	2	2	2
tm: Conexión vaina sensores	►[“GAS/m]	3/4	3/4	3/4	3/4	3/4	3/4	3/4
pc: Conex. ánodos protecc. catódica	►[“GAS/m]	—	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2	1 1/2
D: Diámetro exterior	►[mm]	1160	1360	1660	1660	1660	1910	1910
H: Altura total	►[mm]	2320	2280	2015	2305	2580	2310	2710
Boca de hombre	►[DN]	400	400	400	400	400	400	400
Resistencia eléctrica (opcional)	►[kW]	—	6 ó 9	6 ó 9	6 ó 9	6 ó 9	6 ó 9	6 ó 9