




DESCRIPTION

# 51CE/2

M x M end "Extra Compact" full port ball valve with red steel lever.

Conform to **EN 13828**

DIMENSIONS



D	½"	¾"	1"
d	15	20	25
H	39	49	52
I	12	13	14
L	56	67.5	76.5
R	75	95	95
Weight [g]	190	300	450

Dimensions in **mm**

All threads are conform to ISO 228 standard

MATERIALS

<b>Body</b>	CW617N (EN 12165) CuZn40Pb2 External nickel plated
<b>Ball</b>	CW617N (EN 12165) CuZn40Pb2 Chromium plated
<b>Stem</b>	CW614N (EN 12164) CuZn39Pb3
<b>Stuffing box</b>	CW614N (EN 12164) CuZn39Pb3
<b>Seat</b>	2 x PTFE + 1 x PTFE seal on the stem
<b>O-Rings</b>	2 x FKM
<b>Handle</b>	Delta Protect coated steel. PVC grip with "Pad printing"


APPROVALS



RECOMMENDED WORKING TEMPERATURE/PRESSURE LIMITS

28 bar – 100°C – non shock  
10 bar – 150°C – non shock

PRESSURE DROP DIAGRAM



Dim.	1/2"	3/4"	1"
Kv	14.5	30	45
PN	28	28	28

TEMPERATURE / PRESSURE DIAGRAM

